


Your Search: Name : Pilot Sport Cup



Pilot® Sport Cup

Ultra-High Performance Sport

 Summer Tire

Developed to meet the needs of top car manufacturers. This tire is original equipment on specialty performance vehicles such as the Porsche GT3 RS, BMW M3 and Dodge Viper ACR.






Benefits of This Tire:

- Impressive performance — lap after lap.
- Powerful cornering.
- Race-like reflexes.

Average User Rating:



Michelin Performance Ratings:

				
Wear Life 4/10	Fuel Efficiency 3/10	Handling 10/10	Braking 10/10	Comfort 4/10

Tire Warranties:



Warranties



Standard Limited Warranty (All Michelin® Tires)

All Michelin® tires have a Standard Manufacturer's Limited Warranty, which covers defects in workmanship and materials for the life of the original usable tread, or for 6 years from date of purchase, whichever occurs first. See warranty for details.

TechSpecs

Part #	Tire Size	Load Index	Speed Rating	Sidewall	Runflat	Tread Markings	Mileage Warranty	UTQG Treadwear, Traction, Temp	Rim Width Range (Min / Max)	Section Width (On Measuring Rim Width)	OE Marking	OE Code	Overall Diameter	Revs Per Mile	Tread Depth (in 32nds)	Max Load, Single (@PSI)	Tire Weight
87503	225/40ZR18	88	(Y)	BSW			None	80, AA, A	7.5" - 9"	9.2" on 8"			25.1	834	6	1235@51	20.48
53827	235/40ZR18	91	(Y)	BSW			None	80, AA, A	8" - 9.5"	9.5" on 8.5"			25.4	819	6	1356@51	21.43
60480	265/35ZR18	93	(Y)	BSW			None	80, AA, A	9" - 10.5"	10.9" on 9.5"			25.2	831	6	1433@51	23.48
81118	285/30ZR18	93	(Y)	BSW			None	80, AA, A	9.5" - 10.5"	11.4" on 10"			25.1	834	6	1433@51	24.54
80852	295/30ZR18	94	(Y)	BSW			None	80, AA, A	10" - 11"	12.1" on 11"	C1	DC	25.2	833	6	1477@51	24.82
07299	235/35ZR19	87	(Y)	BSW		DT	None	80, AA, A	8" - 9.5"	9.5" on 8.5"	N1	P	25.47	817	6	1201@51	19.93
88851	235/35ZR19	87	(Y)	BSW			None	80, AA, A	8" - 9.5"	9.5" on 8.5"	*	BM	25.5	816	6	1202@51	21.01
21439	245/35ZR19	89	(Y)	BSW		DT	None	80, AA, A	8" - 9.5"	9.8" on 8.5"	N1		25.79	807	5.5	1279@51	20.19
94325	245/35ZR19/XL	93	(Y)	BSW		DT	None	80, AA, A	8" - 9.5"	9.8" on 8.5"	*	BM	25.79	807	6	1433@50	20.99
65562	265/30ZR19	89	(Y)	BSW		DT	None	80, AA, A	9" - 10"	10.7" on 9.5"	*	BM	25.3	822	6	1279@51	22.95
15839	265/35ZR19/XL	98	(Y)	BSW			None	80, AA, A	9" - 10.5"	10.7" on 9.5"	*	BM	26.34	790	6	1653@50	24.25
32048	P285/30ZR19/LL	87	(Y)	BSW	ZP		None	80, AA, A	9.5" - 10.5"	11.4" on 10"	TPC	GM	25.8	807	5	1201@51	27.65
07839	305/30ZR19/XL	102	(Y)	BSW		DT	None	80, AA, A	10.5" - 11.5"	12.3" on 11"	N1	P	26.26	792	6	1874@50	26.52
54909	305/30ZR19/XL	102	(Y)	BSW		DT	None	80, AA, A	10.5" - 11.5"	12.3" on 11"	N0	P	26.3	790	6	1873@50	26.46
73334	325/30ZR19	101	(Y)	BSW		DT	None	80, AA, A	11" - 12"	13" on 11.5"	N1	P	26.73	778	5.5	1819@51	28.13
29636	325/30ZR19	101	(Y)	BSW		DT	None	80, AA, A	11" - 12"	13" on 11.5"	N2	P	26.73	778	5.5	1819@51	28.11
92516	325/30ZR19	101	(Y)	BSW		DT	None	80, AA, A	11" - 12"	13" on 11.5"	N0	P	26.73	778	6	1819@51	28.66
06610	345/30ZR19	105	(Y)	BSW			None	80, AA, A	11.5" - 12.5"	13.8" on 12"	C1	DC	27.2	765	6	2039@51	31.68
02423	245/30ZR20/XL	90	(Y)	BSW		DT	None	80, AA, A	8" - 9"	9.8" on 8.5"			25.83	805	6	1323@50	23.35
26244	315/25ZR20/XL	99	(Y)	BSW		DT	None	80, AA, A	11.5" - 12.5"	13.2" on 12"			26.38	788	6	1709@51	26.46
10321	P335/25ZR20/LL	94	(Y)	BSW	ZP		None	80, AA, A	11.5" - 12.5"	13.5" on 12"	TPC	GM	26.6	782	6	1477@51	31.81

OE [Vehicle Manufacturer] Sidewall Marking: * = BMW, N0, N1, N2 = Porsche, C1 = Chrysler/Dodge, TPC=GM

OE Code [Original Equipment Key]: BM=BMW, GM=GM, P=Porsche, DC=DaimlerChrysler

XL = Extra Load

DT = Differentread

>> The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height (affecting overall diameter), and +/-4% of the section width.

>> Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

>> Tread patterns are often tuned to accommodate different tire widths. Tires for a particular dimension of a given tire line may vary in appearance from the tire shown in the photograph.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160km/h (100 mph), load and inflation must be adjusted according to the table below.

(Y)-Speed Rated Sizes:

Maximum Speed (mph) 118 124 130 136 143 149 155 161 168 174 180 186

Inflation Increase (psi) 0 0 0 0 1.5 3 4.5 6 7.5 7.5 7.5 7.5

Load Capacity (% of max) 100 100 100 100 100 100 100 100 100 95 90 85

For speeds above 186 mph (300 kph), consult your vehicle manufacturer and tire dealer.